

REXC series

12REXC70

Narada®



Feature

- Design life 20 years
- Combine the advantage of lead acid battery and supercapacitor
- Ideal for PSOC cycle application
- High power, rapid charge/discharge
- Reduce sulfation of negative plate, excellent recharge acceptance performance
- Waterproof, anti-salt treatment, shockproof module installation design
- Comply with IEC60896, IEC61427 etc. standard


Application

- Home energy storage system
- Smart power grids and microgrid system
- Distributed energy storage system
- Hybrid energy storage system such as solar and wind
- Solar power generation grid/off-grid energy storage system
- Emergency lighting system
- Generator and battery hybrid energy system
- Other standby, cycling system

Parameter

Nominal Voltage	12V
Capacity	70Ah (100hr to 1.85V/cell @25°C)
	60Ah (10hr to 1.80V/cell @25°C)
Typical Weight	30kg
Internal Resistance	Approx 9.79mΩ (acc. to IEC60896-21 clause 6.3)
Short-Circuit Current	1291A
Self Discharge	Residual capacity is above 90% after 90 days storage(25°C)
Temperature Ranges	Operation(recommended): 15°C~25°C
	Operation(maximum): -20°C~50°C
Max. charging current	18A
Max. constant charging current	12A
Charge Voltage	Floating: 2.25V/cell(25°C)
	Equalizing/Cycle: 2.30V/cell(25°C)
Terminal	M8 embedded copper
Terminal Hardware Torque	>10N.m

Dimension




Constant Current Discharge Characteristics Units: Amperes(25°C)

End voltage per cell	60min	3hour	5hour	8hour	10hour	24hour	48hour	72hour	120hour
1.75V	33.93	15.60	10.83	7.59	6.33	2.82	1.46	1.00	0.63
1.80V	31.77	15.12	10.59	7.44	6.18	2.77	1.42	0.98	0.62
1.83V	29.76	14.64	10.32	7.32	6.06	2.71	1.39	0.95	0.61
1.85V	28.68	14.34	10.23	7.23	6.00	2.68	1.39	0.95	0.60
1.88V	27.48	14.04	10.11	7.14	5.97	2.66	1.37	0.94	0.60
1.90V	25.47	13.44	9.84	6.96	5.82	2.62	1.34	0.92	0.58


Discharge Data with Constant Power Units: Watts per cell(25°C)

End voltage per cell	15min	30min	1hour	2hour	3hour	4hour	5hour	6hour	8hour	10hour
1.75V	148.11	111.78	68.52	44.91	32.07	26.31	22.35	19.23	14.73	12.36
1.80V	134.67	108.21	66.93	44.10	30.93	25.47	21.72	18.69	14.34	12.18
1.83V	127.53	102.66	64.53	42.30	30.18	25.08	21.27	18.12	14.07	11.94
1.85V	123.90	97.38	60.87	40.50	29.31	24.48	20.73	17.70	13.86	11.70
1.88V	111.45	91.29	57.21	37.65	28.29	23.64	20.04	17.07	13.50	11.40


Discharge curve at different rate (25°C)




Charge curve (25°C)




Capacity vs OCV curve




Residue capacity vs storage time



Capacity vs temperature curve



Design life vs temperature



ABDULMAJEED AL-WAHBANI TRADING GROUP (ATG)
YEMEN SANA'A HADA STREET NEAR AL-GARASI BUILDING
TEL: 211764 MOB: 777222725
WEB SITE WWW.ATG-YE.COM
E-MAIL INFO@ATG-YE.COM

مجموعة عبدالمجيد الوهباني للتجارة
اليمن - صنعاء - حدة جوار عمارة الغراسي
تلفاكس / 211764 جوال 777222725
الموقع الإلكتروني WWW.ATG-YE.COM
البريد الإلكتروني INFO@ATG-YE.COM